

What is claimed is:

1. A method for fitting a surface to a point group using a computer, comprising the steps of:

5 a first step for judging reliability of the point group and

a second step for changing the method for fitting the surface to the point group based on a result of the judgment of reliability obtained in the first step.

AI 10 2. The method according to claim 1, wherein the first step comprising judging reliabilities of points composing the point group, and

the second step comprising changing the method for fitting the surface to the point group by varying a weight of each of the points based on the reliability of each of 15 the points.

3. The method according to claim 1, wherein data indicating reliabilities of the point group and the points are obtained by three-dimensional measurements.

20 4. A device for fitting a surface to a point group using a computer, comprising:

an obtaining section for determining reliability of each of points composing the point group and

25 a modifying section for varying a degree of the fitting of the surface to the point group depending on the reliabilities.

5. The device according to claim 4, comprising:

a weighting section for assigning a weight for each of the points based on the reliability of each of the points, wherein

30 the modifying section changes a degree of the

fitting of the surface to the point group depending on the weights.

6. The device according to claim 4, wherein the surface has been prepared in advance of the fitting.

7. The device according to claim 4, wherein an amount of data for the surface is smaller than that of the point group.

8. The device according to claim 4, wherein the data of the surface includes attribute information associated with form information.

9. The device according to claim 8, wherein the data of the surface represents a form of a face, and the attribute information represents characteristic parts of the face.

10. A system comprising:
a measuring unit for measuring a distance therefrom to a plurality of points on a surface of an object;
a calculator for calculating reliabilities of respective distances of the measured distances;

a processor for modifying prepared data which represents a three-dimensional form using the reliabilities so that a three-dimensional form represented by the modified data resembles a form of the object.

11. A computer program for fitting a surface to a point group that enables a computer to perform the steps of

a first step for judging a reliability of the point group and

a second step for changing the method for fitting

the surface to the point group based on a result of the judgment of reliability obtained in the first step.

12. A processor comprising:

an obtaining section for obtaining original data
5 generated by measurements;

a first modifying section for modifying a first standard model based on the obtained data, the first standard model being previously prepared independently of the obtaining of original data;

10 a second modifying section for modifying a second standard model based on an effect of the modification of the first standard model, the second standard model being relative to the first standard model.

13. The processor according to claim 12, wherein
15 the first standard model is a model for skin and the second standard model is a model for skeleton or a model for muscle, the original data being data whose object is a surface of a human head.

14. The processor according to claim 12, wherein
20 the first standard model has a plurality of construction points corresponding to which a plurality of control points are defined;

the second standard model has a plurality of construction points corresponding to which some of the
25 control points defined by the first standard model are defined;

the first standard model is modified in accordance with movements of the construction points which move in accordance with movements of the control points; and
30 the second standard model is modified in accordance

with movements of the construction points which move in accordance with movements of the control points.

15. The processor according to claim 14, wherein
the control points for moving the construction
5 points of the second standard model are corrected when
adopting a result of the modification of the first
standard model.

16. The processor according to claim 14, wherein
defined as control points corresponding to the
10 construction points of the second standard model are
control points corresponding to construction points among
the construction points of the modified first standard
model which are the closest to the construction points of
the second standard model.

17. The processor according to claim 14, wherein
defined as control points corresponding to
15 construction points of the second construction points are
control points corresponding to points obtained by
projecting the construction points of the second standard
20 model on the first standard model.

18. A process comprising the steps of:
obtaining original data generated by measurements;
modifying a first standard model which has been
prepared separately from the obtaining of the original
25 data based on the obtained original data; and
modifying a second standard model corresponding to
the first standard model based on a result of the
modification of the first standard model.

19. The process according to claim 18, wherein
30 the first standard model has a plurality of

construction points, and a plurality of control points are defined corresponding to the construction points;

the second standard model has a plurality of construction points and some of the control points defined
5 by the first standard model are defined corresponding to the construction points;

the first standard model is modified in accordance with movements of the construction points which move with the control points move; and

10 the second standard model is modified in accordance with movements of the construction points which move with the control points move.

20. A processor comprising:

an obtaining section for obtaining original data
15 generated by measurements;

a storage section for storing a first data representing a standard skin model of a human head and a second data representing a standard skeleton model or a standard muscle model of the human head, the first data
20 and the second data are corresponding to each other; and

a processing section for modifying the first data and the second data so that the standard skin model and the standard skeleton model or standard muscle model fit with the measured surface form.

25 21. A computer program for modeling, which enables a computer to perform the steps of:

obtaining original data generated by measurements;

modifying a first standard model which has been prepared separately from the obtaining of the original
30 data based on the obtained original data; and

modifying a second standard model corresponding to the first standard model based on a result of the modification of the first standard model.

22. A device for modifying a surface based on a three-dimensional point group comprising:

a selection section for selecting a plurality of partial areas from the point group and

a modifying section for modifying a surface based on a point group of each of the selected partial areas.

23. A method for generating a three-dimensional model comprising:

selecting a plurality of partial areas from measurement data obtained by measuring an object and modifying a three-dimensional model based on the measurement data of each of the selected partial areas.

24. A modeling device for generating a three-dimensional model comprising:

a selection section for selecting a plurality of partial areas from measurement data obtained by measuring an object and

a modifying section for modifying a three-dimensional model based on a measurement data of each of the selected partial areas.

25. The device according to claim 24, wherein the modifying section performs modification with respect to the standard model based on the whole measurement data before performing modification based on the measurement data of each of the partial areas.

26. The device according to claim 24, wherein control points for modifying the standard model is

defined on the standard model, and

at least one of the control points, reduction rate
for reducing a number of measurement data and evaluation
function for determining a degree of modification of the
5 standard model is changed.

27. A computer program for generating a three-
dimensional model that enables a computer to perform steps
of:

selecting a plurality of partial areas from
10 measurement data obtained by measuring an object; and
modifying a three-dimensional standard model based
on measurement data of each of the selected partial areas.

add
AI

15

AI
Cml

11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32 33 34 35 36 37 38 39 40 41 42 43 44 45 46 47 48 49 50 51 52 53 54 55 56 57 58 59 60 61 62 63 64 65 66 67 68 69 70 71 72 73 74 75 76 77 78 79 80 81 82 83 84 85 86 87 88 89 90 91 92 93 94 95 96 97 98 99 100